

UKCA – Safety declaration of conformity

Daikin Europe N.V.

declares under its sole responsibility that the products to which this declaration relates:

LREQ5B7Y1\*, LREQ6B7Y1\*, LREQ8B7Y1\*, LREQ10B7Y1\*, LREQ12B7Y1\*, LREQ15B7Y1\*, LREQ20B7Y1\*,  
LREQ15B7Y1R\*, LREQ20B7Y1R\*,

\* = , , 1, 2, 3, ..., 9, A, B, C, ..., Z

are in conformity with the following directive(s) or regulation(s), provided that the products are used in accordance with our instructions:

- S.I. 2016/1105: Pressure Equipment (Safety) Regulations 2016\*\*  
S.I. 2008/1597: Supply of Machinery (Safety) Regulations 2008\*\*\*  
S.I. 2016/1091: Electromagnetic Compatibility Regulations 2016\*
- as amended,

following the provisions of: BS EN 60335-2-40,

\* as set out in <A> and judged positively by <B> according to the **Certificate <C>**.  
\*\* as set out in the Technical Construction File <D> and judged positively by <E> (Applied module <F>). <G>. Risk category <H>. Also refer to next page.

<A>	DAIKIN.TCF.023C9/06-2012
<B>	—
<C>	—
<D>	Daikin.TCFP.001
<E>	HPI-CEproof Ltd. (NB1521)
<F>	D1
<G>	—
<H>	II

\*\*\* Daikin Europe N.V. is authorised to compile the Technical Construction File.

UKCA – Safety declaration of conformity

continuation of previous page:

Design Specifications of the products to which this declaration relates:

Maximum allowable pressure (PS): <K> (bar)

Minimum/maximum allowable temperature (TS\*):

\* TSmin: Minimum temperature at low pressure side: <L> (°C)

\* TSmax: Saturated temperature corresponding with the maximum allowable pressure (PS): <M> (°C)

Refrigerant: <N>

Setting of pressure safety device: <P> (bar)

Manufacturing number and manufacturing year: refer to model nameplate

<K>	PS	38 bar
<L>	TSmin	–50 °C
<M>	TSmax	60 °C
<N>	R410A	
<P>		38 bar

Name and address of the Notified body that judged positively on compliance with the Pressure Equipment (Safety) Regulations: <Q>

<Q>	HPI-CEproof Ltd. The Manor House Howbery Business Park Wallingford OX10 8BA United Kingdom
-----	---